



Typ: DSTU

Dreiphasen-Universal-Spartransformator
 nach DIN/VDE 0550 (bis 5kVA)
 nach DIN/VDE 0532 (ab 6,3kVA)
 stehende Bauform
 PRI-Spannung: 380/400/415/440/460/500V
 SEC-Spannung: 230V
 Frequenz: 50/60 Hz
 Isolationsklasse: T40/F
 Schutzart: IP00 (geeignet zum Einbau bis IP23)
 Zulassung: UL-konform-optional
 Korrosionsschutz durch Harzimpregnierung
 Andere Spannungen oder Schaltgruppen auf
 Anfrage lieferbar.

Type: DSTU

Three-phase universal autotransformers
 constructions according to DIN/VDE 0550 (up to 5kVA)
 constructions according to DIN/VDE 0532 (from 6,3kVA)
 vertical version
 PRI-voltage: 380/400/415/440/460/500V
 SEC-voltage: 230V
 frequency: 50/60 Hz
 insulation class: T40/F
 type of protection: IP00 (suitable for installation up to IP23)
 recognition: UL- conformity -optional
 impregnated against rust with resin
 the transformers are also available with other voltages or
 vector groups corresponding to your wishes

Leistung power kVA	Best.(BV) Nr./ order No.	Maße /dimensions(mm)							Gewicht weight Kg.
		A	B	C	D	E	F	GØ	
0,5	50600	150	90	165	100	70	70	6	5,5
0,63	50601	180	95	190	125	80	65	7	7,0
0,8	50602	180	105	190	125	80	75	7	8,5
1,0	50603	180	115	190	125	80	85	7	10,0
1,3	50604	205	120	210	145	95	85	7	11,5
1,6	50605	205	130	210	145	95	95	7	13,0
2,0	50606	240	130	260	170	110	100	11	18,0
2,5	50607	240	140	260	170	110	110	11	21,0
3,2	50608	240	150	260	170	110	120	11	24,5
4,0	50609	300	140	325	210	140	110	11	30,5
5,0	50610	300	155	325	210	140	125	11	36,0
6,3	50611	300	165	325	210	140	135	11	42,0
8,0	50612	335	175	365	230	160	145	11	53,0
10,0	50613	360	175	395	250	170	145	11	58,0
13,0	50614	360	190	395	250	170	160	11	68,0
16,0	50615	360	205	395	250	170	175	11	78,0
20,0	50616	420	215	450	280	190	165	14	92,0
25,0	50617	480	195	500	356	-	158	13	135,0
32,0	50618	480	222	500	356	-	185	13	173,0
40,0	50619	580	255	540	400	270	205	18	175,0
50,0	50620	580	265	540	400	270	215	18	195,0