



Typ: DLT 23

Dreiphasen-Leistungstransformatoren
in Stahlblechgehäuse IP23- RAL7032
nach DIN/VDE 0550 und 0532
getrennte Wicklungen
Frequenz: 50/60 Hz
Isolationsklasse: T40/F
Schirmwicklung zwischen PRI- und SEC-Wicklung
eingebautem Temperaturbegrenzer (Öffner)
Zulassung: CSA 22.2/66-1/2 UL 5085-1/2-optional
kompakte Bauform
für feste Installation
Korrosionsschutz durch Harzimprägnierung
Andere Spannungen oder Schaltgruppen auf Anfrage
lieferbar.

Type: DLT 23

Tree-phase power transformers
sheet-steel enclosure-type of protection IP23
construction according to DIN 0532/5050
separate windings
frequency: 50/60 Hz
insulation class: T40/F
shielding winding between PRI- and SEC-winding
built-in thermal cut-out (break contact)
recognition: CSA 22.2/66-1/2 UL 5085-1/2-optional
compact version
for fixed installation
impregnated against rust with resin
the transformers are also available with other voltages
or vector groups corresponding to your wishes

Leistung Power kVA	Best.(BV)Nr./order No.						Maße/dimensions(mm)							Gewicht weight Kg.
	400V	200V	400V	440V	460V	500V	A	B	C	D	E	FØ	Pg	
	230V	400V	400V	400V	400V	400V								
032	55620	55640	55660	55680	55700	55720	225	275	200	195	245	7,5	16	8,5
0,4	55621	55641	55661	55681	55701	55721	225	275	200	195	245	7,5	16	9,5
0,5	55622	55642	55662	55682	55702	55722	225	275	200	195	245	7,5	16	11,0
0,63	55623	55643	55663	55683	55703	55723	225	275	200	195	245	7,5	16	12,5
0,8	55624	55644	55664	55684	55704	55724	225	275	200	195	245	7,5	16	14,5
1,0	55625	55645	55665	55685	55705	55725	225	275	200	195	245	7,5	16	17,0
1,3	55626	55646	55666	55686	55706	55726	275	350	180	245	300	8,5	16	23,5
1,6	55627	55647	55667	55687	55707	55727	275	350	180	245	300	8,5	16	26,5
2,0	55628	55648	55668	55688	55708	55728	275	350	180	245	300	8,5	16	30,0
2,5	55629	55649	55669	55689	55709	55729	325	450	240	270	395	11	16	38,0
3,2	55630	55650	55670	55690	55710	55230	325	450	240	270	395	11	16	43,5
4,0	55631	55651	55671	55691	55711	55731	325	450	240	270	395	11	16	49,5