



Typ: EN01-S und EN02-S

Einphasen-Gleichstromversorgungen
 mit Schnappbefestigung für Trageschiene TS35
 Eingangsspannung: 230/400 +/-20VAC
 Frequenz: 50/60 Hz
 Ausgangsspannung: 12/24V/DC
 Restwelligkeit (RW): 48% (Typ EN01-S)
 : <5% (Typ EN02-S)
 Sicherheitstransformator nach DIN/VDE 0551
 Isolationsklasse: T40/B
 Schutzart: IP00
 Schutzbeschaltung für Gleichrichter
 berührungssichere Klemmen
 Schutzleiteranschluss
 Korrosionsschutz durch Harzimprägnierung
 Andere Ausführungen auf Anfrage lieferbar.

Type: EN01-S und EN02-S

Single-phase power supplies
 With snap-on fixing suitable for mounting rail TS35
 input voltage: 230/400 +/-20VAC
 frequency: 50/60 Hz
 output voltage: 12/24V/DC
 residual ripple (RW): 48% (Typ EN01-S)
 : <5% (Typ EN02-S)
 safety isolating transformer according to DIN/VDE 0551
 insulation class: T40/B
 type of protection:: IP00
 suppressor circuit to protect the rectifier
 the terminals are protect against accidental contact
 according to VBG4
 safety earth connection
 impregnated against rust with resin
 the power supplies are also available with other
 constructions corresponding to your wishes

Leistung Power W	Spannung voltage V	Strom current A	RW %	Best.(BV)Nr. /order No.	Maße/dimensions(mm)				Gewicht weight Kg.
					A	B	C	D	
36	12	3	48	51934	78	74	82	-	1,3
48	12	4	48	51935	84	74	112	-	1,7
72	12	6	48	51936	84	88	112	-	2,1
96	12	8	48	51937	96	87	142	-	2,4
120	12	10	48	51938	96	97	142	-	2,9
144	12	12	48	51939	96	110	142	-	3,6
36	24	1,5	48	51954	78	74	82	-	1,3
48	24	2	48	51955	84	76	87	-	1,6
72	24	3	48	51956	84	90	87	-	2,0
96	24	4	48	51957	96	87	142	-	2,4
120	24	5	48	51958	96	97	142	-	2,9
144	24	6	48	51959	96	110	142	-	3,6
36	24	1,5	5	51914	78	74	82	-	1,4
48	24	2	5	51915	84	76	87	-	1,7
72	24	3	5	51916	84	90	87	-	2,1
96	24	4	5	51917	96	87	142	-	2,6
120	24	5	5	51918	96	97	142	-	3,1
144	24	6	5	51919	96	110	142	-	3,8