



Typ: EN 01

Einphasen-Gleichstromversorgungen  
 Eingangsspannung: 230/400 V +/-20V/AC  
 Frequenz: 50/60 Hz  
 Ausgangsspannung: 12/24V/DC  
 Restwelligkeit: 48%  
 Sicherheitstransformator nach DIN/VDE 0551  
 Isolationsklasse: T40/B  
 Schutzart: IP00  
 Schutzbeschaltung für Gleichrichter  
 Berührungssichere Anschlussklemmen  
 Schutzleiteranschluss  
 frei zugängliche Befestigungslöcher  
 Korrosionsschutz durch Harzimpregnierung  
 Andere Ausführungen auf Anfrage lieferbar.

Type: EN 01

Single-phase power supplies  
 input voltage : 230/400 V +/-20V/AC  
 frequency: 50/60 Hz  
 output voltage: 12/24V/DC  
 residual ripple: 48%  
 safety isolating transformer according to DIN/VDE 0551  
 insulation class: T40/B  
 type of protection: IP00  
 suppressor circuit to protect the rectifier  
 the terminals are protect against accidental contact  
 according to VBG4  
 safety earth connection  
 the fixing holes are easily accessible  
 impregnated against rust with resin  
 the power supplies are also available with other  
 constructions corresponding to your wishes

Leistung Power W	Spannung Voltage V	Strom current A	Best.(BV) Nr./order No.	Maße/dimensions(mm)							Gewicht weight Kg.
				A	B	C	D	E	FØ	G	
36	12	3	51660	78	70	85	65	52	4,5	-	1,3
48	12	4	51661	84	74	115	70	56	4,5	-	1,7
72	12	6	51662	84	88	115	70	70	4,5	-	2,1
96	12	8	51663	96	82	145	80	70	5,5	-	2,4
120	12	10	51664	96	92	145	80	80	5,5	-	2,9
144	12	12	51665	96	105	145	80	94	5,5	-	3,6
180	12	15	51666	120	100	165	100	78	6,5	-	4,2
240	12	20	51667	120	112	165	100	90	6,5	-	5,2
300	12	25	51668	120	120	165	100	98	6,5	-	6,2
36	24	1,5	51669	78	70	85	65	52	4,5	-	1,3
48	24	2	51670	84	74	90	70	56	4,5	-	1,6
72	24	3	51671	84	88	90	70	68	4,5	-	2,0
96	24	4	51672	96	82	145	80	70	5,5	-	2,4
120	24	5	51680	96	92	145	80	80	5,5	-	2,9
144	24	6	51681	96	105	145	80	94	5,5	-	3,6
192	24	8	51682	120	100	165	100	78	6,5	-	4,2
240	24	10	51683	120	112	165	100	90	6,5	-	5,2
360	24	15	51684	135	120	190	113	98	7,5	-	6,5
480	24	20	51685	135	130	190	113	108	7,5	-	7,5
600	24	25	51686	135	150	190	113	128	7,5	-	9,5